

# 48X16X48X

## CD-RW Drive *BCE 4816IM*

- **Write at 48X speed, Rewrite at 16X speed, Read at 48X speed**
- **Standard E-IDE/ATAPI interface, easy to install**
- **Support all kinds of CD formats**
- **Support Buffer Underrun Prevention technology**



### Technical Specifications:

- Interface E-IDE/ATAPI
- Disc capacity 74min/650MB, 80min/700MB
- CD formats CD-DA, CD-ROM, CD-ROM XA, CD-I, Photo CD, CD-TEXT, Video CD, CD-Extra, CD-R, CD-RW, CD-UDF
- Writing methods TAO (Track at Once), DAO (Disc at Once), SAO (Session at Once), Multi-Session, Packet Writing
- Writing speed CD-R 7200KB/sec (48X, CAV)  
CD-RW 2400KB/sec (16X, CLV)
- Data transfer rate CD-ROM/RW 7200/4800 KB/sec (CAV)  
Audio Extraction up to 40X
- Access time Average <100 msec
- MTBF 125,000 POH (20% duty cycle with read mode)
- Disc loading Tray (motorized)
- Dimensions (WxHxD) 148.6 x 41.8 x 193.3 mm
- Weight 1 Kg
- Operating temperature 5°C ~ 45°C



**BTC** 英群企業股份有限公司  
BEHAVIOR TECH COMPUTER CORP.

Headquarters:  
Taiwan office: TEL: (886)-2-8768-3988  
FAX: (886)-2-8768-3777

U.S. Office:  
California: TEL: (1)-510-657-3956  
FAX: (1)-510-657-3965

European Offices:  
The Netherlands: TEL: (31)-10-264-2444 FAX: (31)-10-264-2458  
France: TEL: (33)-1-4670-1978 FAX: (33)-1-4670-1897

<http://www.btc.com.tw>

\* Specifications are subject to change without notice.  
\* All company and product names are trademarks of their respective owners.