

BTC 5109AU

Entry Level Keyboard



Electrical Characteristics

- Model selection : USB
- Input power : 5Vdc, 50 mA
- Switch activation mechanism : Membrane
- Serial data output : Serial format, TTL level compatible

Operating Conditions

- Operating temperature : 0° to 50° C
- Storage temperature : -40° to 70° C
- Humidity : 20% to 90%, non-condensing
- Altitude : -1000 ft to 10000 ft

System Requirements

- IBM PC compatible.
- Available USB port.
- Microsoft®, Windows®98SE/ME/2000 or XP operating system.

Physical & Mechanical Characteristics

- Model number (key numbers) : BTC 5109AU (104/105)
- Languages : U.S. / European
- Connector : USB
- Travel distance : 3.5 +/- 0.5mm
- Peak load before make (normal key) : 55 +/- 20 g
- Dimension : 463(L) X 201(W) X 29.5(H)mm
- Weight : 0.67 kg

Packing Information

- 1pc/box : 474(L) X 180(W) X 35(H) mm
: 0.75 kg
- 10 pc/carton : 490(L) X 380(W) X 215(H) mm
: 8.7 kgs
- Container load : 3,780pcs / 20'; 8,820 pcs / 40'

Electromagnetic Characteristics (EMC)

- EMI : FCC part 15, subpart B, Class B, BSMI
- CE

- IBM, PC and PS/2 are registered trademarks of International Business Machines Corporation.
- Microsoft, Windows, and the Windows Logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

BTC[®] BEHAVIOR TECH COMPUTER CORP.

<http://www.btc.com.tw>

Headquarters
Taiwan Office:
TEL: (886)-2-8768-3988
FAX: (886)-2-8768-3777

U. S Office
California:
TEL: (1)-510-657-3956
FAX: (1)-510-657-1859

European Office
France:
TEL: (33)-1-4670-1978
FAX: (33)-1-4670-1897

Netherlands:
TEL: (31)-10-264-2444
FAX: (31)-10-264-2458

PRINT IN TAIWAN / 2006 01