

52x32x52x**CD-RW Drive BCE 5232IM**

- **Write at 52X speed, Rewrite at 32X speed, Read at 52X speed**
- **Standard E-IDE/ATAPI interface, easy to install**
- **Support all kinds of CD formats**
- **Support Buffer Underrun Prevention technology**

**Technical Specifications:**

- Interface E-IDE/ATAPI
- Disc capacity 74min/650MB, 80min/700MB
- CD formats CD-DA, CD-ROM, CD-ROM XA, CD-I, Photo CD, CD-TEXT, Video CD, CD-Extra, CD-R, CD-RW, CD-UDF
- Writing methods TAO (Track at Once), DAO (Disc at Once), SAO (Session at Once), Multi-Session, Packet Writing
- Writing speed CD-R 7800KB/sec (52X, CAV)
CD-RW 4800KB/sec (32X, PCAV)
- Data transfer rate CD-ROM/RW 7800/4800 KB/sec (CAV)
Audio Extraction up to 40X
- Access time Average <100 msec
- Data buffer 2 MB
- MTBF 125,000 POH (20% duty cycle with read mode)
- Disc loading Tray (motorized)
- Dimensions (WxHxD) 148.6 x 41.8 x 193.3 mm
- Weight 1 Kg
- Operating temperature 5°C ~ 45°C
- Mounting method Horizontal & Vertical

**BTC** 英群企業股份有限公司
BEHAVIOR TECH COMPUTER CORP.Headquarters:
Taiwan office: TEL: (886)-2-8768-3988
FAX: (886)-2-8768-3777U.S. Office:
California: TEL: (1)-510-657-3956
FAX: (1)-510-657-3965European Offices:
The Netherlands: TEL: (31)-10-264-2444 FAX: (31)-10-264-2458
France: TEL: (33)-1-4670-1978 FAX: (33)-1-4670-1897<http://www.btc.com.tw>

* Specifications are subject to change without notice.
* All company and product names are trademarks of their respective owners.