

LED Tube (4 feet)

BTC- LI01- 1198W- 1(Daylight)/ BTC- LI01- 1198Y- 1(Warm White)

Features



- Supply Voltage : 100VAC~240VAC
- No starter applied. Replace the traditional fluorescent tube directly.
- Quick lighting up, no flicker.
- Aluminum alloy main body helps better heat dissipation.
- Specific optical design enhances high light efficiency and light shape. No glare.
- No UV and radiation.
- Low power consumption, save more energy and Save more money.
- No pollution, and recyclable. Conforms to ROHS compliant.
- Compatible with T8/T10 lighting fixture.
- Operating temperature : -30°C~45°C
- Storage temperature : -40°C~80°C
- Long life (**Max 40,000 hours at ambient temperature 25°C**)
- Able to be used in office illumination, home

Specifications

LED Type	1W Hi-Power LED * 16 pcs
Color Temperature	(White) 5600~6300K (Warm White) 3800~4500K
Base Type	T8&T10
Dimension	φ 35mm x1200mm
Input Voltage	100~240 Vac
Power Consumption	23 W max
Constant Current	350mA+/-10%
Operating Temperature	-30°C ~ +45°C
Storage Temperature	-40°C ~ +80°C
Weight/Unit	624g
Beam Angle	90°
Luminous Flux (typical)	1088~1280 lm
Color Rendering Index	70%
Illuminance	197 Lux (2 tubes at 3.5M height)
Illuminance	153 Lux (2 tubes at 4.0M height)
Lifetime	Max 40,000 hr
Optics	Double optics of optical lens and lampshade
Housing	Aluminum alloy

